

CLOUD PRINTER GAINSCHA GA-E200I

Print method	Direct Thermal Line
Print resolution	203dot/inch
Printing Width	72mm or 80mm
Dot Density	576dot/line or 640dot/line
Print speed	200mm/s
Interface type	Ethernet+Wi-Fi Cloud+USB Audio
Thermal Paper Spec.	paper width: 79.5 ±0.5mm, Paper outer diameter : Φ 100mm
Line spacing	3.75mm (can be adjust by Command)
Number of columns	Font A-42 line or 48line / Font B-5 line or 64line / Simplified/Traditional Chinese-21line or 24 line
Character Fonts	Standard obtained GB18030 Chinese Fonts, Korean and Japanese fonts, support vector font download
Character Size	ANK Fonts, Font A:1.5x3.0mm(12x24dot), Font B:1.1x2.1mm(9x17dot)
	Simplified/Traditional Chinese : 3.0x3.0mm(24x24dot)
Extended Character Table	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/
	(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128
Cash drawer output	DC 24V/1A
Power adaptor	DC 24V/2A
Power supply	Input: AC110V/220V,50~60Hz,Output : DC 24V/2A
Printer dimensions	180mmx140mmx145mm
Working environment	Temperature: 5~45°C , Humidity: 10~80%
Storage environment	Temperature: -10~50°C , Humidity: 10~90% (RH)
Reliability	150KM for Mechanism, 1.5 Million Cuts