

## CLOUD PRINTER GP-CH0421D

<b>Printing</b>	Print Mode	Direct thermal
	Print Speed	2-8 inch/s
	Interface	USB+USB HOST + Ethernet
	Resolution	203dots/inch (8dots/mm)
	Dot Size	0.125x0.125mm (1mm=8dots)
	Print Width	Max 104mm (4.09")
	Print Length	2286mm (90")
	Print Head	Temperature sensor: thermal sensitive resistance
		Position sensor: microswith
	Memory	DRAM: 2M FLASH: 2M
	Pulse excitation	1X10*
Printer language	EPL	
<b>Media</b>	Paper Roll OD	130mm OD
	Paper Type	Continuous paper , paper with interspaces , folding paper ,black mark paper etc.
	PaperRolling Up Method	Printing side outward rolling
	Paper Width	Max. 120mm (4.72") Min. 20mm (0.78")
	Paper Thickness	Max. 0.254mm (10mil) Min. 0.06mm (2.36mil)
	Paper Roll Core Size	25.4mm~38mm (1"~1.5")
	Paper Gap	Min. 2 mm (0.09")
	Label Length	10~2286mm (0.39"~90")
	Remark: If label length is less than 25.4mm(1 inch), the label paper with perforated line are recommended in order to tear off the labels easily.	
<b>Physical properties</b>	Weight	2.09kg
	Dimension	285*210*180mm(W*D*H)
<b>Environment</b>	Work Environment	Temperature: 5 ~ 45°C, Humidity: 25 ~ 85%
	Storage Environment	Temperature: -10 ~ 50°C, Humidity: 10 ~ 90%
<b>Reliability</b>	Print head	30KM
<b>Power</b>	Power Supply	The built-in voltage automatic switching power supply
		Input: AC 110V/240V, Output: 50 ~ 60Hz, DC 24V/2A