

## CLOUD PRINTER GAINSCHA GP-TD2270

Print consumables	thermal paper, gap paper, black mark paper, continuous paper	
Applicable Scene	Supermarket, food takeaway, catering, medical, clothing, tea, baking chain stores, etc.	
Print method	Label	Receipt
Print command	TSPL	ESC/POS Command
Print resolution	203DPI	203DPI
Print width	56mm (max)	48mm (max)
Print speed	127mm/s (max)	90mm/s
Memory	FLASH: 60K	FLASH: 60K
Print head temperature detect	Thermistor	Thermistor
Paper detect	photoelectric sensor	photoelectric sensor
Printer Interfaces	USB+Wi-Fi	USB+Wi-Fi
Graphics	Monochrome BMP and other image files can be downloaded to FLASH	Support different density bitmap printing, ASCII Fonts
1D Barcode / 2D Barcode	CODE128/EAN128/ITF/CODE39/CODE93/EAN13/EAN13+2/EAN13+5/EAN8/EAN8+2/EAN8+5/CODEBAR/UPC_AU/PCA+2/UPCA+5UPC_E/UPCE+2/UPC_E+5/QRCODE	UPC_A/UPC_E/JAN13(EAN13)/JAN8 (EAN8) /CODE39/CODEBAR/ITF/CODE93/CODE128/QRCode
Character Fonts	Commonly used single-byte fonts, FONT0 to FONT8, GB18030 Fonts, Simplified/Traditional Chinese, Korean	ANK Fonts FontA: 12*24dot FontB: 9*17dotSimplified/Traditional Chinese, Korean:24*24dot
Character Enlargement / Rotation	1 ~10 times enlargement in portrait and landscape orientation; 0°, 90°, 180°, 270°degree rotation	1 ~8 times enlargement in portrait and landscape orientation, rotating printing, inverted printing
Media type	Thermal Paper Roll / Adhesive thermal paper	Thermal Paper Roll
Media width	25-60mm (with back paper)	57.5±0.5mm
Media diameter	80mm (max)	80mm (max)
Media thickness	Max 0.25mm; Min 0.06mm	
Media output method	Top paper output	
Power input	DC8.5V 3A	
Cash drawer output	DC 12V/1A	
Working environment	5~45°C (41~113°F) , 25~85%RH	
Storage environment	5~45°C (41~113°F) , 25~85%RH	
Printer weight	0.50kg	
Printer dimensions	174mm×138mm×128mm	
Packing dimension	240mm×150mm×135mm	
Print head (reliability)	30km	
Printer certificate	CCC	
* The above parameters are subject to change without notice.		