




Strong Scalability | Easy to Use | Ultra-fast Recognition | HD Speaker Audio | Fast Payment

MANTRA



www.mantratec.com



Mantra Softech, an Indian technology company, has unveiled its innovative Payment Sound Box.

With the Payment Sound Box, customers are immediately notified when their payment is accepted or declined, which can help reduce the time spent waiting in lines and increase overall customer satisfaction by bringing transparency.

By leveraging the power of QR code-based payment technology, the payment sound box has the potential to revolutionize the way businesses and customers interact during the payment process.

Features

- R Integrated user friendly design
- ැටු Over The Air (OTA) firmware updates for DFOTA & Music Files
- Instant Sound Notification for payment transaction, ((_)) Battery, Device and Network.
- 二: Loud 85db sound output for clear communication

Smart Applications













LED indication for Network and Battery



7-Segment display feature to show received amount (Optional)



Restaurant

Entrance

Scenic Spot Convenience Store

Toll Parking station lot

Supermarket

SOUNDBOX FOR INSTANT AUDIO PAYMENT CONFIRMATION

Small and portable speaker for your daily payment alerts on every payment you receive through any QR Code or UPI app

Specification

÷	CPU ARM® Dual-core Cortex-A5, 500MHz	
	SIM Card Slot 1x Micro Sim Card	
	Communication 2G (EGSM900/DCS1800) 4G (LTE-FDD:B1/B3/B5/B8 & LTE-TDD:B34/B38 /B39/B40/B41) Wi-Fi 2.4GHz (Optional)	
•	Button 1x Power key, 1x Reset key, 2x Volume Up & Down key, 1x Function Key	
Ċ	Power Supply DC 5V / 1A	
2	Dimensions Device Dimensions (L x W x H) : 112 x 100 x 73 mm	
7		

	Memory RAM: 16MB & FLASH: 24MB
ズビ	Display 7 Segment LED Display (6 - Digit)
Ļ	LED Indication 1x Battery status, 1x Network Connectivity
4 /2	OTA DFOTA and Music file Update Over The Air
r ();	Speaker 4 Ohm 3W (Adjustable Volume)
Θ	Peripheral Ports 1x Powered USB TYPE-C
KG	Weight Device WeightApprox : 0.28 Kg
₿ ₩	Environmental Operating Temperature: 0°C to +50°C Storage Temperature:-10°C to +70°C Humidity (Operating / Storage) : 5% - 95% RH, Non-condensing
- 15kV	

MANTRA





≤ sales@mantratec.com ⊕ www.mantratec.com

Copyrights Mantra Softech (India) Pvt Ltd. All Rights Reserved.