



GoIP4

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:47:28
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:18:36

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base Station

Event Triggers

Tools

Advance SIP

SIP Listening Port Mode	<input type="text" value="Fixed"/>
Port	<input type="text" value="5060"/>
Line Selection Mode	<input type="text" value="Round Robin"/>
SIP INVITE Response	<input type="text" value="SIP 183"/>
SIP Header Via	<input type="text" value="Socket"/>
SIP Busy Code	<input type="text" value="603"/>
Get Callee Number	<input type="text" value="By To Header"/>
Call OUT Auth Mode	<input type="text" value="None"/>
Built-in SIP Proxy	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Password	<input type="text" value="demo"/>
Dynamic Concurrence Capabilities	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
NAT Keep-alive	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
DTMF Signaling	<input type="text" value="Outband"/>
Outband DTMF type	<input type="text" value="RFC 2833"/>
RTP Payload Type	<input type="text" value="101"/>
Signaling QoS	<input type="text" value="None"/>
Signaling Encryption	<input type="text" value="None"/>
Signaling NAT Traversal	<input type="text" value="None"/>

[Advanced Timing>>](#)

[GSM-SIP Code Map>>](#)



GoIP4

Logout

SN(Serial Number):4MFRM18041722
 Firmware Version: GST1610-1.01-62-4
 Module Version: M35FAR02A01_RSIM
 Uptime: 03:46:38
 Last Login Time: 2018-08-07 17:07:26
 Current Time: 2018-08-07 17:17:45

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base Station

Event Triggers

Tools

SIP

Config Mode	<input type="text" value="Single Server Mode"/>
Authentication ID	<input type="text" value="demo"/>
Password	<input type="password" value="••••"/>
SIP Proxy	<input type="text" value="192.168.1.197"/>
SIP Registrar Server	<input type="text" value="192.168.1.197"/>
Re-register Period (s)	<input type="text" value="60"/>
Phone Number	<input type="text"/>
Display Name	<input type="text"/>
Outbound Proxy	<input type="text"/>
Home Domain	<input type="text"/>
Backup Server	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Prefix Match Mode	<input type="radio"/> Match Caller <input checked="" type="radio"/> Match Callee
Delete Callee Prefix while Dialing	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Routing Prefix	<input checked="" type="radio"/> Line 1 <input type="radio"/> Line 2 <input type="radio"/> Line 3 <input type="radio"/> Line 4
Line 1 Routing Prefix	<input type="text"/>
	<input type="text" value="*Auto Config Other lines"/>





GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:50:43
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:21:50

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base
Station

Event Triggers

Tools

Call In Auth

CH1 CH2 CH3 CH4

Call IN Auth

White/Black List:(A comma-separated list of numbers)

For Call Party Numbers



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:49:25
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:20:33

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base
Station

Event Triggers

Tools

Call In

User No Input Timeout(s)

CID Forward Mode

CID Prefix

CH1 CH2 CH3 CH4

Call IN via GSM Enable Disable

Forwarding to VoIP Number

Dial Plan

GSM Call Waiting

Hunt Group Mode

Auto Incoming Call Block Enable Disable

Save Changes



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:50:01
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:21:08

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base Station

Event Triggers

Call Out Auth

CH1 CH2 CH3 CH4

Call OUT Auth

White/Black List:(A comma-separated list of numbers)

For Call Party Numbers



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:48:42
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:19:50

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base
Station

Event Triggers

Tools

Call OUT

GSM Auto Redial

Enable Disable

Outbound Memory

Enable Disable

GSM Dial Timeout(s)

GSM None Ringback Timeout(s)

CH1

CH2

CH3

CH4

Call OUT via GSM

Enable Disable

Forwarding to Number

Dial Plan

Restricted Dial Plan

Enable Disable

When calls occurs, Deactivate the line for - seconds, Call type:



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:53:07
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:24:14

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base Station

Event Triggers

Event Triggers

ACD(?) < <input type="text"/> Seconds	Down the module
ASR(?) < <input type="text"/> %	Down the module
Every <input type="text"/> Minutes	Null
# of consecutive call attempts with no ringback tones >= <input type="text"/>	Disable VoIP of the lin
# of consecutive unanswered calls >= <input type="text"/>	Disable VoIP of the lin
# of consecutive short calls (interval < <input type="text"/> S)>= <input type="text"/>	Disable VoIP of the lin
# of consecutive fast-answered calls (interval < <input type="text"/> S)>= <input type="text"/>	Null

Save Changes



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
 Firmware Version: GST1610-1.01-62-4
 Module Version: M35FAR02A01_RSIM
 Uptime: 03:41:41
 Last Login Time: 2018-08-07 17:07:26
 Current Time: 2018-08-07 17:12:49

Status

Summary

General

SIM

SIM Call Forward

Configurations

Tools

Hardware

S/N	4MFRM18041722	Firmware	GST1610-1.01-62-4
Model	GoIP4	Local Time	2018-08-07 17:12:49

Network

LAN Port	192.168.1.197	LAN MAC	38:3F:10:05:69:58
PC Port	192.168.8.1	PPPoE	DISABLED
Gateway	192.168.1.3	DNS Server	8.8.8.8

Web Record

Last Client	192.168.1.224	Last Login Time	2018-08-07 17:07:26
Current Client	192.168.1.224		

Call Status and Setting

VoIP				GSM				
Line	Mode	Login	Routing Prefix	CH	Login	Call In	Call Out	Remain Time
1	S	N		1	Y	Y	Y	NO LIMIT
2	S	N		2	N	Y	Y	NO LIMIT
3	S	N		3	N	Y	Y	NO LIMIT
4	S	N		4	N	Y	Y	NO LIMIT



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:52:00
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:23:08

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base
Station

Event Triggers

Tools

IMEI

Line1 IMEI

Line2 IMEI

Line3 IMEI

Line4 IMEI

IMEI Auto Change

Set Random IMEI When Module PowerUp



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:48:07
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:19:14

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base
Station

Event Triggers

Tools

Media

RTP Port Range	<input type="text" value="16384"/> - <input type="text" value="32768"/>
PacketLength (ms)	<input type="text" value="20"/>
Jitter Buffer	<input type="text" value="Adaptive"/>
MinDelay	<input type="text" value="40"/>
MaxDelay	<input type="text" value="360"/>
Media QoS	<input type="text" value="None"/>
Media Encryption	<input type="text" value="None"/>
Media NAT Traversal	<input type="text" value="None"/>
RTP Disconnect Detect(s)	<input type="text" value="0"/>

Audio Codec Preference>>



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:45:36
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:16:44

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base
Station

Event Triggers

Tools

Network Configuration

LAN Port	Static IP	PC Port	Router mode
IP Address	192.168.1.197	IP Address	192.168.8.1
Subnet Mask(optional)	255.255.255.0	Subnet Mask	255.255.255.0
Default Route	192.168.1.3	DHCP Server	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Primary DNS	8.8.8.8	Advanced>>	
Secondary DNS(optional)	8.8.4.4		
802.1q VLAN	<input type="radio"/> Enable <input checked="" type="radio"/> Disable		
PPTP VPN	<input type="radio"/> Enable <input checked="" type="radio"/> Disable		
Advanced>>			
PING	<input type="radio"/> Disable <input checked="" type="radio"/> Enable		

Save Changes



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:44:49
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:15:57

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base Station

Event Triggers

Tools

Preferences

Language (语言) English

Time Zone GMT+8

Time Server pool.ntp.org

Auto-provision Enable Disable

Remote Control

Web Access Security>>

Save Changes

Network Tones China

DDNS Enable Disable

Auto Reboot Enable Disable

Reboot Time 04:00

Auto Reset CDR Enable Disable

IVR Enable Disable

Remote Server Enable Disable

SMPP SMSC Enable Disable



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:43:56
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:15:04

Status

Summary

General

SIM

SIM Call Forward

Configurations

Tools

SIM Call Forward

CH	Always	Busy	No Answer	No Service
1	OFF	OFF	OFF	OFF
2	Not Set	Not Set	Not Set	Not Set
3	Not Set	Not Set	Not Set	Not Set
4	Not Set	Not Set	Not Set	Not Set



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
Firmware Version: GST1610-1.01-62-4
Module Version: M35FAR02A01_RSIM
Uptime: 03:51:22
Last Login Time: 2018-08-07 17:07:26
Current Time: 2018-08-07 17:22:30

Status

Configurations

Preferences

Network

Basic VoIP

Advance VoIP

Media

Call Out

Call Out Auth

Call In

Call In Auth

SIM

SIM Forward

IMEI

SMS

GSM Carrier

GSM Base
Station

Event Triggers

Tools

SIM Forward

CH1 CH2 CH3 CH4

GSM Call Forward

Always Set Disable Not Set

Busy Set Disable Not Set

No Answer Set Disable Not Set

No Service Set Disable Not Set



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
 Firmware Version: GST1610-1.01-62-4
 Module Version: M35FAR02A01_RSIM
 Uptime: 03:43:21
 Last Login Time: 2018-08-07 17:07:26
 Current Time: 2018-08-07 17:14:29

Status

Summary

General

SIM

SIM Call

Forward

Configurations

Tools

GSM									
Remote SIM: DISABLE									
CH	SIM	GSM	RSSI	GPRS Login	GPRS Attach	Carrier	BSC Mode	BCCH	Cell&LAC
1	Y	Y	31	Y	Y	Vodafone - Gujarat	AUTO		LAC:16B,CELL ID:3A21
2	N	N	31	N	N		AUTO		
3	N	N	31	N	N		AUTO		
4	N	N	31	N	N		AUTO		
GSM Detail									
CH	Module	Firmware Version	SIM Number	IMEI	IMSI	ICCID			
1	M35	M35FAR02A01_RSIM		865794039206786	404051153626924	8991052160522418095F			
2	M35	M35FAR02A01_RSIM		865794039213444	404241023097216				
3	M35	M35FAR02A01_RSIM		865794039185857					
4	M35	M35FAR02A01_RSIM		865794039185865					



GoIP4

简体中文

Logout

SN(Serial Number):4MFRM18041722
 Firmware Version: GST1610-1.01-62-4
 Module Version: M35FAR02A01_RSIM
 Uptime: 03:40:40
 Last Login Time: 2018-08-07 17:07:26
 Current Time: 2018-08-07 17:11:48

Status

Summary

General

SIM

SIM Call

Forward

Configurations

Tools

Summary																						
CH	Line	M	SIM	GSM	VOIP	Status	SMS	ACD(S)	ASR(%)	Duration	Count	CDR Start	RSSI	Carrier	BCCH	Idle	Remain	Count Remain	SMS Remain	Reset		
<input type="checkbox"/>	1	Y	Y	Y	N	IDLE		35	60	34m	33/59	2018-05-17 19:16:13	31	Vodafone - Gujarat		139	NO LIMIT	NO LIMIT	NO LIMIT	<input type="button" value="Remain"/>	<input type="button" value="SMS"/>	<input type="button" value="ACD&ASR"/>
<input type="checkbox"/>	2	Y	N	N	N	IDLE		35	2	1m	1/37	2018-07-13 21:10:48	31			219	NO LIMIT	NO LIMIT	NO LIMIT	<input type="button" value="Remain"/>	<input type="button" value="SMS"/>	<input type="button" value="ACD&ASR"/>
<input type="checkbox"/>	3	Y	N	N	N	IDLE					0/0	2018-08-07 13:31:23	31			219	NO LIMIT	NO LIMIT	NO LIMIT	<input type="button" value="Remain"/>	<input type="button" value="SMS"/>	<input type="button" value="ACD&ASR"/>
<input type="checkbox"/>	4	Y	N	N	N	IDLE					0/0	2018-08-07 13:31:23	31			219	NO LIMIT	NO LIMIT	NO LIMIT	<input type="button" value="Remain"/>	<input type="button" value="SMS"/>	<input type="button" value="ACD&ASR"/>
<input type="checkbox"/>	All																			<input type="button" value="Remain"/>	<input type="button" value="SMS"/>	<input type="button" value="ACD&ASR"/>